

# ANHUI OMI VINYL CO.,LTD.

## TEST REPORT

**REPORT NUMBER**

190422011SHF-002

**ISSUE DATE**

2019/5/9


**PAGES**

5

**DOCUMENT CONTROL NUMBER**

LFT-APAC-SHF-OP-10k

© 2018 INTERTEK



## Test Report

Issue Date: 2019/5/9 Intertek Report No. 190422011SHF-002

Applicant: ANHUI OMI VINYL CO.,LTD.

Applicant Address: 5,WUYASHAN WEST ROAD,LANGXI EDZ,XUANCHENG,ANHUI 242100,CHINA

Attn: Feng Zhao

**SUBJECT:** Performance testing  
EVP(E-SPC Vinyl FLOORING)

Dear Sir,

This test report represents the results of our evaluation of the above referenced product(s) to the requirements contained in the following standards:

TEST METHODS AND STANDARDS
Refer to the next following Pages.

SAMPLE ID	MODEL	SPECIFICATION
S190422011SHF.001	7MP	1220X181X7mm+1mm IXPE

SAMPLE RECEIVED: 2019/4/11  
TESTED FROM: 2019/4/22 TO 2019/5/9

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

# Test Report

Issue Date: 2019/5/9

Intertek Report No. 190422011SHF-002

**Test Items, Method and Results:**

Test method: ASTM E492-09(2016)<sup>e1</sup>

Temperature: 19 °C


Relative Humidity: 80 %

Specimen area: 12.5 m<sup>2</sup>

Volume of the receiving room: 104 m<sup>3</sup>

Floor-ceiling assembly: The system consisted of 150mm thick concrete floor with a drop ceiling below forming the horizontal separation between two room, one directly above the other. The drop ceiling consisted of 350mm deep light steel bar joists spaced 1200mm on centre. Two layers of 12mm thick gypsum boards were fixed on the bar. 50mm thick glass wool batts were placed in the 350mm space. The 7.8mm E-SPC Vinyl FLOORING (including 1mm IXPE) were placed on the concrete floor.

Frequency (Hz)	Ln (dB)
100	58
125	57
160	53
200	54
250	53
315	52
400	49
500	47
630	44
800	43
1000	41
1250	39
1600	35
2000	32
2500	29
3150	25
IIC=	62



**Calculated Impact Insulation Class: IIC 62**

Note:

1. Ln = Normalized Sound Pressure Level for Covering over Floor System
2. Classified IIC in accordance with ASTM E989-12, Standard Classification for Determination of Impact Insulation Class.
3. The IIC was for the whole floor-ceiling assembly system.

## Test Report

Issue Date: 2019/5/9

Intertek Report No. 190422011SHF-002

### Test Photos:



Test set up



Ceiling assembly

## Test Report

Issue Date: 2019/5/9

Intertek Report No. 190422011SHF-002

### APPENDIX: SAMPLE RECEIVED PHOTO



### REPORT AUTHORIZED

When signed with physical or electronic signature, the contents of this report have been prepared and approved per Intertek's quality process in accordance with ISO 17025.

  
Name: Jodie Zhou  
Title: Reviewer

  
Name: Mason Wang  
Title: Project Engineer



### Revision:

NO.	DATE	CHANGES	AUTHOR	REVIEWER
190422011SHF-002	2019/5/9	First issue	Mason Wang	Jodie Zhou